Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

(Currently Amended) A granular substance characterized by comprising:
a matrix composed of a nonmagnetic insulating organic material; and
ferromagnetic metal particles dispersed in said matrix and having a mean particle
size of 50 nm or less.

wherein the volume ratio of said matrix <u>in said granular substance</u> is in the range of 5 to 50%.

- 2. (Original) The granular substance according to claim 1, characterized in that said ferromagnetic metal particles are formed of a metal mainly comprising at least one element selected from Fe, Co and Ni.
- 3. (Original) The granular substance according to claim 1, characterized in that said ferromagnetic metal particles are formed of a metal mainly comprising Fe and Co.
- 4. (Original) The granular substance according to claim 3, characterized in that the concentration of Co in said metal mainly comprising Fe and Co is in the range of 10 to 50 at%.
- 5. (Original) The granular substance according to claim 1, characterized in that said ferromagnetic metal particles are spaced apart by a distance enabling exchange coupling therebetween.

Appl. No. 10/541,096 Amdt. Dated May 29, 2008

Reply to Office Action of March 4, 2008

Attorney Docket No. 81864.0069 Customer No.: 26021

6. (Original) The granular substance according to claim 1, characterized in that

said matrix is formed of an organic polymer.

7. (Original) The granular substance according to claim 1, characterized in that

the volume ratio of said matrix is in the range of 5 to 40%.

8. (Original) The granular substance according to claim 1, characterized in that

said granular substance is in the form of a film, and has a complex permeability the real

part (μ ') of which is 40 or more at 1 GHz, a quality factor Q (Q = μ '/ μ " where μ " is the

imaginary part of the complex permeability) of 1 or more, and a saturation

magnetization of 5 kG or more.

9. (Original) The granular substance according to claim 8, characterized in that

the real part of the complex permeability (μ) is 50 or more at 1 GHz.

10. (Original) The granular substance according to claim 8 or 9, characterized in

that the quality factor Q (Q = μ' / μ'' where μ'' is the imaginary part of the complex

permeability) is 5 or more.

11. (Original) The granular substance according to claim 8 or 9, characterized in

that the saturation magnetization is 6 kG or more.

12. (Original) The granular substance according to claim 1, characterized in that

the resistivity is 100 $\mu\Omega$ cm or more.

13 - 16 (Cancelled)

Appl. No. 10/541,096 Amdt. Dated May 29, 2008 Reply to Office Action of March 4, 2008 Attorney Docket No. 81864.0069 Customer No.: 26021

17. (Currently Amended) A magnetic device having a magnetic thin film for high frequency,

characterized in that said magnetic thin film for high frequency is formed of a granular substance comprising;

a matrix composed of a nonmagnetic insulating organic material; and ferromagnetic metal particles dispersed in said matrix and having a mean particle size of 50 nm or less,

wherein the volume ratio of said matrix <u>in said granular substance</u> is in the range of 5 to 50%.

- 18. (Original) The magnetic device according to claim 17, characterized in that the mean particle size of said ferromagnetic metal particles is in the range of 5 to 30 nm.
- 19. (Original) The magnetic device according to claim 17, characterized in that said ferromagnetic metal particles are formed of a metal mainly comprising Fe and Co.
- 20. (Original) The magnetic device according to claim 17, characterized in that said matrix is formed of an organic polymer.
 - 21. (Original) The magnetic device according to claim 20, characterized in that: said organic polymer is a fluorocarbon polymer; and the resistivity of said magnetic thin film for high frequency is 300 $\mu\Omega$ cm or more.
- 22. (Original) The magnetic device according to claim 17, characterized in that said magnetic thin film for high frequency has a complex permeability the real part (μ ') of which is 40 or more at 1 GHz, a quality factor Q (Q = μ '/ μ '' where μ '' is the imaginary

Appl. No. 10/541,096 Amdt. Dated May 29, 2008 Reply to Office Action of March 4, 2008 Attorney Docket No. 81864.0069 Customer No.: 26021

part of the complex permeability) of 1 or more, and a saturation magnetization of 5 kG or more.